

# GLYCERINE FILLABLE MODEL TCS



Suitable for non corrosive applications where the medium will not attack brass or bronze. Ideally suited to harsh environmental conditions, due to the stainless steel case, which can be supplied dry or liquid filled when protection is required against pulsation and or vibration.

Scales are offered in standard kPa / psi dual scale only.

## DIRECT MOUNT P/N TCS-63-AB-15-OF

### MODEL/MOUNTING:

- TCS- **-AB** - Direct mount bottom entry
- TCS- **-CB** - Direct mount centre rear entry
- TCS- **-FB** - Panel mount rear entry ("U" Clamp fixing)

**CASE & BEZEL:** 304 Stainless steel case and clamp bezel fixing IP-65 rating

**DIAMETER:** 63mm

**ACCURACY:** +/- 1.6% of full scale deflection

**BOURDON TUBE:** Phosphor bronze

**CONNECTION:** 1/4" BSPT

**WINDOW:** Plexiglass

**OPTIONS:** Glycerine Filled - **OF**

RANGE	CODE
-100-0 kPa/PSI	01
-100-0-60 kPa/PSI	02
-100-0-150 kPa/PSI	03
-100-0-300 kPa/PSI	04
-100-0-500 kPa/PSI	05
-100-0-900 kPa/PSI	06
0-100 kPa/PSI	09
0-160 kPa/PSI	10
0-250 kPa/PSI	11
0-400 kPa/PSI	12
0-600 kPa/PSI	13
0-800 kPa/PSI	14
0-1000 kPa/PSI	15
0-1600 kPa/PSI	16
0-2500 kPa/PSI	17
0-4000 kPa/PSI	18
0-6000 kPa/PSI	19
0-8000 kPa/PSI	20
0-10000 kPa/PSI	21
0-16000 kPa/PSI	22
0-25000 kPa/PSI	23
0-40000 kPa/PSI	24
0-60000 kPa/PSI	25

P/N EXAMPLE	MODEL	DIAMETER	MOUNTING	CODE	OPTION
	TCS	63	AB	15	OF